

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(12) **UK Patent Application** (19) **GB** (11) **2 196 798** (13) **A**

(43) Application published 5 May 1988

(21) Application No **8725015**

(22) Date of filing **26 Oct 1987**

(30) Priority data

(31) **8625648**

(32) **27 Oct 1986**

(33) **GB**

(71) Applicant

The General Electrical Company p.l.c.

(Incorporated in United Kingdom)

1 Stanhope Gate, London W1A 1EH

(72) Inventors

Alwyn Finney

Michael Whitlam

(74) Agent and/or Address for Service

C F Hoste,

Central Patent Department (Wembley Office), The

General Electric Company p.l.c., Hirst Research Centre,

East Lane, Wembley, Middlesex HA9 7PP

(51) INT CL⁴

H05K 9/00 5/00 7/10

(52) Domestic classification (Edition J):

H1R BH

U1S 2087 H1R

(56) Documents cited

EP A1 0169329

EP A2 0076657

US 4658439

EP A1 0168310

Note: EP A1 0169329 and US 4658439 are equivalent;

(58) Field of search

H1R

Selected US specifications from IPC sub-class H05K

(54) **Housing arrangements for electrical/or electronic equipment**

(57) A housing arrangement for equipment, such as telephone exchange equipment or transmission equipment, in which individual circuit units are formed on printed circuit boards mounted side-by-side on a shelf unit, wherein the shelf unit forms a first electromagnetic screening enclosure 1, and interconnections between said circuit units, and external connections to those units, are made by way of a back plane mounted in a second electromagnetic screening enclosure 2 having one face in common with the first enclosure. Socket connectors for the printed circuit boards are mounted on the back plane and project through apertures in the common face of the enclosures.




Fig. 1

GB 2 196 798 A

1/3

2196798




Fig. 1




Fig. 2

2196798




Fig. 3

2196798




Fig. 4

SPECIFICATION

Housing arrangements for electrical or electronic equipment

5

The present invention relates to housing arrangements for electrical or electronic equipment.

10 In particular, although not exclusively, the invention is concerned with housing arrangements for electrical or electronic equipment, for example telephone exchange equipment or transmission equipment, in which individual electrical or electronic circuits or circuit units
15 are formed on respective ones of a plurality of printed circuit boards mounted side-by-side in parallel planes on a common support structure, the circuits on the respective boards being arranged to be connected by way of respective plug and socket connectors to interconnecting circuits carried on a common back plane.

20 According to one aspect of the present invention in a housing arrangement for electrical or electronic equipment in which a plurality of equipment units are detachably interconnected by way of a common interconnection unit, said equipment units are arranged to be substantially enclosed within a first electromagnetic screening enclosure and said common
30 interconnection unit is arranged to be substantially enclosed within a second electromagnetic screening enclosure.

35 Preferably external connections to said equipment units are made by way of said common interconnection unit within said second enclosure.

40 According to another aspect of the present invention a housing arrangement for electrical or electronic equipment comprises first and second electromagnetic screening enclosures having one face in common, means detachably to mount a plurality of equipment units in said first enclosure, and means in said second enclosure to mount an interconnection unit, said
45 common face being provided with apertures for plug and socket type connectors whereby said equipment units may be detachably connected to said interconnection unit.

50 Preferably said equipment units are provided with electromagnetic screening front panels which together complete a front face of said first enclosure.

55 According to another aspect of the present invention electrical or electronic apparatus comprises a first electromagnetic screening enclosure, a plurality of electrical or electronic equipment units, means detachably to mount said equipment units within said first enclosure, a second electromagnetic screening enclosure having one face in common with said first enclosure, interconnecting means within
60 said second enclosure, and respective plug and socket connectors arranged detachably electrically to connect said equipment units to

said interconnecting means through said common face between said enclosures.

70 Preferably said equipment units are provided with front panels which form respective parts of a front face of said first enclosure.

Housing arrangements for electronic equipment in accordance with the present invention will now be described by way of example with reference to the accompanying drawings, of which:-

75 *Figures 1 and 2* show schematically two different forms of housing arrangement.

Figure 3 shows a part-sectional view of part of a housing arrangement, and

80 *Figure 4* shows a detail isometric view of part of a housing arrangement.

In many forms of electronic equipment, such as that used in telephone exchange systems or in transmission systems, individual electronic circuits or circuit units are formed on printed circuit "cards" of standard sizes, which are interconnected and to which external connections are made by means of respective plug and socket type connectors. A plurality of these cards are arranged to be supported side by side on a shelf structure with their general planes vertical and parallel to one another, the upper and lower edges of the cards being located in guide members or runners into which the cards may be introduced by sliding movement from the front of the shelf structure. The respective plug connectors are disposed at the rear of the cards, as positioned within the shelf structure, while the corresponding socket connectors are mounted on a common transverse back-plane which also supports any required interconnecting wiring. Where the equipment requires it several shelves of standard heights, depth and width may be supported one above the other in a rack framework, and two or more rack frameworks may stand side by side.

As the individual circuit units become more compact and as clock-pulse rates and signal frequencies become higher, sensitive circuits have to be screened more carefully from stray electromagnetic fields or radiation which could interfere with their operation, and potential sources have to be screened as far as possible to prevent such radiation from reaching sensitive circuits. Standards are now being set for the levels of radiation screening acceptable in newly installed equipment.

Referring now to Figs. 1 and 2, which show 120 in outline two different shelf structures, the circuit cards (not shown) supported by the shelf structures are housed within a first enclosure 1, while the back plane (not shown) is enclosed within a second enclosure 2. In the case of the structure outlined in Fig. 1 the circuit cards occupy the whole width of the structure, and the enclosure 2 is provided with a downward extension 3 which provides a forward facing surface for external connection points. This extension 3 may have the

same depth as the enclosure 2, as shown in outline, or may extend forward as indicated by the chain-dotted outline 4. The enclosure 2 may alternatively be extended upwards (not shown) to provide the required forward facing surface.

In the case of the structure outlined in Fig. 2, where the circuit cards do not occupy the full width of the structure, so that the enclosure 1 is narrower than the enclosure 2, the unoccupied forward facing surfaces of the enclosure 2 may provide sufficient area for the required external connections. The structure may be provided with side frames 7 at full shelf width, for example for mounting purposes.

As far as possible the two enclosures 1 and 2 are divided from one another by an internal electromagnetic screen member (not shown).

The front face of the enclosure 1 is made up of individual front panels 6 associated with the individual circuit cards. The enclosure 1, and the enclosure 2 if necessary, may be provided with apertures 8 to provide for a flow of cooling air. These apertures 8 may for example be provided in the upper and lower faces of the enclosure 1, and may be arranged in a regular pattern of which only a small part is indicated in Figs. 1 and 2.

Referring now to Figs. 3 the enclosure 1 is made up of upper and lower shelf screen members 9 and 10 which extend between upper and lower horizontal aluminium alloy extrusion members 11, 12, 13 and 14. An internal screen member 15 is secured to the upper and lower screen members 9 and 10, this member 15 being pierced substantially only by the apertures required for socket connectors 16, which are secured to a back plane member 17, and for the rear ends of card runners 18. The enclosure 2 is formed by the member 15, the rear edges of the members 9 and 10, the extrusion members 12 and 14 and a rear shelf screen 19.

The front panel 6 of each printed circuit card 20 is secured to the upper and lower extrusion members 11 and 13 by card retaining screws 21. As shown in Fig. 4 each front panel 6 has its edges 22 formed to lie parallel with its printed circuit card 20 and with the edges of adjacent panel members 6, and electrically conductive spring finger strip, say, of beryllium copper (not shown) is secured to these edges 22 to provide electrical continuity between the front panels 6.

The intervals between any fixing screws or rivets (not shown) used in the assembly of the enclosures 1 and 2, and the dimensions of the apertures 8, are chosen to be much smaller than the wavelength of the highest frequencies expected to be produced or utilised within the enclosures 1 and 2, or those to which electronic circuits within these enclosures may be sensitive, in order to reduce to a specified level any leakage out or in at these

or lower frequencies. In a particular example the intervals between screws or rivets was 50mm or less, and the apertures 8 were 10mm wide and 20mm long, the enclosures providing screening attenuation of 50-60dB up to frequencies of 20MHz.

The larger apertures in the screen member 15, dictated by the dimensions of the sockets 16, may give rise to some leakage, but the effects of this are minimised either by the screening effect of the second enclosure 2, by filtering, or by the use of intermediate screens such as 23 (Fig. 3).

While electromagnetic screening is provided by the almost total enclosure described above, electrostatic screening requires that all the members forming the enclosures 1 and 2 be in good electrically conductive contact with one another. For this purpose the screen members, which may be fabricated for example from aluminium alloy, and the extrusion members, are coated with an electrically conductive corrosion resistant finish.

Any indicator lights, switches or connectors provided in the front panels 6 in general require only small holes in the panels, causing substantially no leakage or radiation at the higher frequencies.

Shelf structures of the forms described above may either be arranged as stand-alone units or may be dimensioned for mounting on any standard rack framework. The front panels 6 may be covered by a full-width transparent cover.

CLAIMS

1. A housing arrangement for electrical or electronic equipment in which a plurality of equipment units are detachably interconnected by way of a common interconnection unit, wherein said equipment units are arranged to be substantially enclosed within a first electromagnetic screening enclosure and said common interconnection unit is arranged to be substantially enclosed within a second electromagnetic screening enclosure.

2. A housing arrangement in accordance with Claim 1 wherein external connections to said equipment units are made by way of said common interconnection unit within said second enclosure.

3. A housing arrangement for electrical or electronic equipment comprising first and second electromagnetic screening enclosures having one face in common, means detachably to mount a plurality of equipment units in said first enclosure, and means in said second enclosure to mount an interconnection unit, said common face being provided with apertures for plug and socket type connectors whereby said equipment units may be detachably connected to said interconnection unit.

4. A housing arrangement in accordance with Claim 3 wherein said equipment units are provided with electromagnetic screening front

panels which together complete a front face of said first enclosure.

- 5 5. Electrical or electronic apparatus comprising a first electromagnetic screening enclosure, a plurality of electrical or electronic equipment units, means detachably to mount said equipment units within said first enclosure, a second electromagnetic screening enclosure having one face in common with said
10 first enclosure, interconnecting means within said second enclosure, and respective plug and socket connectors arranged detachably electrically to connect said equipment units to said interconnecting means through said com-
15 mon face between said enclosures.

6. Electrical or electronic apparatus in accordance with Claim 5 wherein said equipment units are provided with front panels which form respective parts of a front face of said
20 first enclosure.

7. A housing arrangement for electrical or electronic apparatus substantially as hereinbefore described with reference to the accompanying drawings.